The nature of climate.™

Dometic Penguin Low Profile Heat Pumps

Superior technology and innovative design make Penguin Heat Pumps a leader in effective climate control. Fully automated and worry free operation means comforting warmth to 30 degrees. Then the built-in thermostatically controlled (CCCII Thermostat) **changeover activates the LP gas furnace for continuous comfort.**

- 13,500 or high capacity BTUs
- Heats and cools in a single unit
- Low profile — only 9.5-inches high
- Fits standard 14-inch roof vent openings
- Superior performance for ducted or non-ducted systems
- Eco-friendly 410A refrigerant

LIGHTWEIGHT

ECO-FRIENDLY

Dometic

Penguin Low Profile Heat Pumps

The sleek, low profile Penguin Heat Pump is easy to install and operate. It provides consistent, reliable performance that makes it perfect for any RV and lifestyle.

Air Distribution Box

- Five multi-directional air slots
- Ratcheting side vents
- Washable Hepa-style filters

Single Zone LCD Thermostat

- Simple, three-button operation
- Easy control including cool/furnace or heat pump
- Low profile
- Manual or automatic control
- Large display screen

Comfort Control Center II

- Digital
- Large, low profile SMX bluelight display
- Industry first, real time-of-day, area independent programming
- Easily controls rooftop AC, heat pump, furnace, hydronic heating or dehumidifier

Return Air Grill

- Washable filter
- Quick cool air discharge
- Low profile

Features	650015	651815	651816	651916
Nominal capacity, BTU/hr.	13,500	13,500	High Capacity	High Capacity
Installation type	Non-ducted	Non-ducted or Ducted	Non-ducted or Ducted	Non-ducted or Ducted
Electrical rating	120VAC, 60 Hz, 1Ph			
Compressor-rated load amps	12.5	12.5	12.3	12.3
Fan motor-rated load amps	3.5	3.5	3.3	3.3
Compressor-locked rotor amps	61	61	61	61
Fan motor-locked rotor amps	10	10	8.5	8.5
SCFM, high-speed max./min.	325/250	325/250	325/250	325/250
Refrigerant 410A (oz.)	25	25	24	24
Minimum wire size	12 AWG copper up to 24 feet. For distances over 24 feet consult the National Electrical Code.			
AC circuit protection	(User Supplied) 20 amp time delay fuse or 20 HCAR circuit breaker			
DC circuit protection	(User Supplied) Installation must comply with national, state, provincial and/or local electrical codes			
Installed weight, lbs.	99	99	99	99
Minimum generator size - 1 unit	3.5 KW	3.5 KW	3.5 KW	3.5 KW
Minimum generator size - 2 units	5.0 KW	5.0 KW	5.0 KW	5.0 KW
Thermostat/Control options	ADB	Multi-Zone CCCII	Multi-Zone CCCII	Single Zone LCD

Outstanding Warranty

Dometic's 2-Year Protection Plus warranty.

For more information visit www.Dometic.com/USA

Dometic reserves the right to make improvements or modifications without notice.

Printed on recycled paper with 25% post consumer content with environmentally safe ink.

Printed in U.S.A. **©2011 Dometic Corporation** **OS2336 DRV-687/TM/3-11/1.5M**

Dometic