



RH439LD/LDAG (30 liters)

- Automatic defrost
- LED interior light
- One door rack for miniatures
- One door rack for bottles/cans
- Height and tilt adjustable shelves
- Anthracite steel cabinet

These midsized units are equipped with “Fuzzy Logic” energy regulation plus sensor controlled surveillance of the silent absorption cooling unit (CUC system). Fully adjustable shelving and door racks accommodate a wide range of products and container sizes.



RH449LD/LDAG (40 liters)

- Automatic defrost
- LED interior light
- One door rack for miniatures
- One door rack for bottles/cans
- Height and tilt adjustable shelves
- Anthracite steel cabinet

With fully adjustable shelving and door racks, these wider units offer larger capacity with minimal energy use. “Fuzzy Logic” energy regulation and sensor controlled cooling unit surveillance (CUC system) are standard as well as numerous options.



Specifications	RH439LD	RH439LDAG	RH449LD	RH449LDAG
Type	Freestanding or built-in	Freestanding or built-in	Freestanding or built-in	Freestanding or built-in
Door	Décor panel or sliding hinge	Glass with silver trim	Décor panel or sliding hinge	Glass with silver trim
Interior capacity (liters)	1.1 (30)	1.1 (30)	1.4 (40)	1.4 (40)
Dimensions -HxWxD (mm)	21-3/4" x 15" x 17-1/16" (552 x 380 x 434)	21-3/4" x 15" x 17-1/16" (552 x 380 x 434)	22-15/16"* x 16-5/8" x 17-5/16" (582 x 422 x 440)	22-15/16"* x 16-5/8" x 17-5/16" (582 x 422 x 440)
Built in dimensions -HxWxD (mm)	20-5/8" x 15" x 17-1/16" (524 x 380 x 434)	20-5/8" x 15" x 17-1/16" (524 x 380 x 434)	21-13/16" x 16-5/8" x 17-5/16" (554 x 423 x 440)	21-13/16" x 16-5/8" x 17-5/16" (554 x 423 x 440)
Input power (watts)	65	65	65	75
Consumption	.7 kWh / 24 hrs (Per ISO 7371 standard)	1.1 kWh / 24 hrs (Per ISO 7371 standard)	.8 kWh / 24 hrs (Per ISO 7371 standard)	1.1 kWh / 24 hrs (Per ISO 7371 standard)
Weight	29 lbs.	36 lbs.	32 lbs.	36 lbs.
Special Features	Lock or sliding hinge, LED door opening control system, left or right door swing	Lock, LED door opening control system, left or right door swing, 1/2" (12 mm) feet	Lock or sliding hinge, LED door opening control system, left or right door swing	Lock, LED door opening control system, left or right door swing, 1/2" (12 mm) feet
Optional Features	Additional miniature rack, door handle		Additional miniature rack, door handle	