

# SKYVENETIAN 50mm Aluminium Slat

## Order Form and Product Guide

Customer \_\_\_\_\_  
 Address \_\_\_\_\_  
 \_\_\_\_\_

Tel \_\_\_\_\_  
 Mobile \_\_\_\_\_  
 Email \_\_\_\_\_

Order \_\_\_\_\_  
 Quote \_\_\_\_\_  
 Date \_\_\_\_\_  
 Project Name \_\_\_\_\_  
 Project Location \_\_\_\_\_

**Are any of the blinds on this order to be installed where children under 42 months old are likely to be allowed? <sup>2</sup> Yes No**

Please note: we can only supply blinds if the above question has been answered No.

Window ID	Dimension Info	Slat	Head rail Options	Restraint Options	Manual Control Option	Powered Control Options	Qty					
Location	Type Recess <sup>1</sup> Blind	Colour _____	Type 50 mm Powered Only LTWN	Free hanging <b>Guide wire</b> Chrome dome Nickel dome Brass dome Chrome flush Black flush Nickel flush Low profile	<b>Position</b>  Left Right	<b>Motor Code</b>  _____						
	Width (X)		Ladder String					Fixing Top Face	<b>Length<sup>3</sup></b> 400 500 700 1000	<b>Cord Colour</b>  Black Grey Fawn		
	Drop (Y)	Colour (See table on pg 2)									<b>Valance</b> Yes	<b>Cord Tidy</b> (With black or white rubber insert) Chrome - Black White Nickel - Black White
	Installation height <sup>2</sup>											
				<b>Motor Wire Exit Point:</b> Left Right								
					<b>Controlled By:</b> Switch Constant Switch Momentary Somfy remote <sup>4</sup> Dometic remote <sup>4</sup>							

**Notes:**

- If recess size is specified the blind will be made X minus 10mm [3/8"] and Y minus 5mm [1/4"].
- Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500mm [59 1/16"] and a cord collection device (cleat or cord tidy) is fitted at or above this height.
- Continuous cords are supplied with cord tidy child safety device as standard, please select colour.
- Please fill in the Powered Accessories Order Form, download from [here](#).
- Specialist motor please contact Dometic before ordering.

**Motor codes & specifications (Other motors available please contact manufacturer for details)**

Voltage	Motor Code	Description	Switched (SW) or remote controlled (R)	Torque Nm	RPM	Min width X (mm)	Max drop Y(mm)	Head rail size	
								50mm	TWIN
12 V DC	O38TW11	Atlantic 12R	SW / R	1.2	26	650 mm [25 9/16"]	3000 mm [118 1/8"]	✓	N/A
24 V DC	O38TW12	Atlantic 24R							
24 V DC	LTWN	Lutron Twin	See note 6	See note 5	See note 5	624 mm [24 9/16"]	3250 mm [127 15/16"]	N/A	✓
24 V DC	S30D / S30R	Somfy Sonesse 30 DCT / RTS	SW / R	2	28	616 mm [24 1/4"]	3250 mm [127 15/16"]	✓	N/A
230 V AC	S40W/ S40R	Somfy Sonesse 40 WT / RTS	SW / R	9	12				
230 V AC	40W4	Pacific 230R WT 230v AC	SW	10	16				

A selection of simple shapes are available, please contact Dometic for more details.

Internal use only Customised



# SKYVENETIAN 50mm Aluminium Slat

# Order Form and Product Guide

### Head rail

A 50mm steel headrail is used as standard and is available in the following standard colours.


- White    Black    Brown
- Vanilla    Silver

An aluminium headrail and custom painting service are both available upon request, please contact Dometic for more details.

### Head rail Colour Options

		Headrail Type	
		VB25	VB50
<b>Standard Colour</b>	White	✓	✓
	China White		✓
	Black	✓	✓
	Brown	✓	✓
	Beige		✓
	Vanilla	✓	
	Silver	✓	

Custom colours are available, contact manufacturer for more details



### Valance

Front facing Valance will be automatically colour and size matched based on order.

### Cord Tidy

#### Mandatory child safety device

Fix to an adjacent wall, ensures taut chain or continuous cord.  
Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



### Guide wire Hold down options

#### Dome:

Chrome or Brushed Nickel

#### Flush Mounted:

Chrome, Brushed Nickel or Black



### ST6 Side Track

Used to increase privacy, improve room darkening and help keep blinds secure

