SKYVENETIAN 50mm Wood slat

Order Form and Product Guide

Customer	Tel	Order	Quote	Date
Address	Mobile	Project Name		
	Email	 Project Location		

Are any of the blinds on this order to be installed where children under 42 months old are likely to be allowed?² Yes No

Please note: we can only supply blinds if the above question has been answered No.

Window ID	Dimension	Slat	Head rail	Restraint	Manual Control Options	Powered	Qty
	Info		Options	Options	Cord Loop ³	Control Options	
	Type Recess ¹	Colour	Type 50 mm	Free hanging Guide wire	Position: Left Right	Motor Code	
Location	Blind Width (X)	Ladder	Powered Only LTWN	Chrome dome Nickel dome Brass dome	Length (mm): ³ 400 500 700 1000	Motor Wire Exit Point:	
	Drop (Y)	_ String	Fixing Top Face	Chrome flush Black flush Nickel flush Low profile	Cord Colour Black Grey Fawn	Left Right Controlled By:	
	Installation height ²	_	Colour (See table on pg 2)	ST6 Sidetracks White Black Custom	Cord Tidy (With black or white rubber insert) Chrome - Black White	 Switch Constant Switch Momentary Somfy remote⁴ Dometic remote⁴ 	
			Valance Yes No	- RAL Ref	Nickel - Black White		

Notes:

- 1. If recess size is specified the blind will be made X minus 10mm [3/8"] and Y minus 5mm [1/4"].
- Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500mm [59 ^{1/16}"] and a cord collection device (cleat) is fitted at or above this height.
- 3. Continuous cords are supplied with cord tidy child safety device as standard, please select colour.
- 4. Please fill in a Powered Accessories Order Form.
- 5. Specialist motor please contact manufacturer before ordering.

A selection of simple shapes are available, please contact manufacturer for more details.

Wood Venetian blinds are not suitable in areas of high humidity, toilets, bathrooms or wet rooms. Please consult manufacturer regarding alternative solutions for these areas.

Motor codes & specifications (Other motors available please contact manufacturer for details)

Val	Voltage Motor Code Description	Switched (SW) or	Torque	RPM	Min width	Max drop	Head rail size			
VOI	lage	Motor Code	Description	remote controlled (R)	Nm	RPIN	X (mm)	Y(mm)	50mm	TWIN
12	V DC	038TW11	Atlantic 12R	SW / R	1.2	26	650 mm [25 ^{9/16} "]	3000 mm [118 1/8"]	~	N/A
24 \	V DC	038TW12	Atlantic 24R	SW/R	1.2	20	650 mm [25 %]	5000 mm [118 **]	Ì	IN/A
24	V DC	LTWN	Lutron Twin	See note 6	See note 5	See note 5	624 mm [24 9/16"]	3250 mm [127 ^{15/16} "]	N/A	~
24	V DC	S30D / S30R	Somfy Sonesse 30 DCT / RTS	SW / R	2	28				
230	V AC	S40W/ S40R	Somfy Sonesse 40 WT / RTS	SW / R	9	12	616 mm [24 1/4"]	3250 mm [127 15/16"]	~	N/A
230	V AC	40W4	Pacific 230R WT 230v AC	SW	10	16				



A> DOMETIC

SKYVENETIAN 50mm Wood slat

Cord Tidy

Mandatory child safety device Fix to an adjacent wall, ensures taut chain or continuous cord.

Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



Guide wire hold down options

Dome: Chrome or Brushed Nickel

Flush mounted: Chrome, Brushed Nickel or Black


Valance


Front facing Valance will be automatically colour and size matched based on order.



ST6 Side Track

Used to increase privacy, improve room darkening and help keep blinds secure.





Head rail Colour Options

		Headra	Headrail Type		
		VB25	VB50		
Standard Colour	White	~	~		
	China White		~		
	Black	~	~		
	Brown	~	~		
	Beige		~		
	Vanilla	~			
	Silver	×			

Custom colours are available, contact manufacuter for more details

