## SKYVENETIAN 25mm Wood slat

### **Order Form and Product Guide**

Customer	Tel	Order	Quote	Date
Address	Mobile	Project Name		
	Email	 Project Location		

#### Are any of the blinds on this order to be installed where children under 42 months old are likely to be allowed? Yes No

Please note: we can only supply blinds if the above question has been answered No.

Window ID	Dimension Info		Headrail Options	Restraint Options	Manual Control Options	Powered Control Options Motor Options	Qty
	Type Recess <sup>1</sup>	Colour	Type 25mm (Default)	Free hanging Guide wire	Position: Left Right	Code:	
Location	Blind Width (X)	Ladder	50mm Fixing Top	Chrome dome Nickel dome Brass dome Chrome flush	Length (mm): <sup>3</sup> 400 500 700 1000	Motor Wire Exit Point: Left Right	-
	Drop (Y)	String	Face Colour	Black flush Nickel flush Low profile	Cord Colour Black Grey Fawn	Controlled By: Switch Constant Switch Momentary	
Slat Colour	Installation		(See table on pg 2)	ST6 Sidetracks White Black Custom	<b>Cord Tidy</b> (With black or white rubber insert)	Somfy remote <sup>4</sup> Dometic remote <sup>4</sup>	
	height <sup>2</sup>		Valance	RAL Ref	Chrome - Black White Nickel - Black White		
			Yes No				

#### Notes:

- 1. If recess size is specified the blind will be made X minus 10mm [3/8"] and Y minus 5mm [1/4"].
- Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500mm [59<sup>1/16</sup>"] and a cord collection device (cleat or Cord tidy) is fitted at or above this height.
- 3. Continuous cords are supplied with cord tidy child safety device as standard, please select colour.
- 4. Please fill in the Powered Accessories Order Form.

A selection of simple shapes are available, please contact Dometic for more details.

Wood Venetian blinds are not suitable in areas of high humidity, toilets, bathrooms or wet rooms. Please consult Dometic regarding alternative solutions for these areas.

### Motor codes & specifications (Other motors available please contact manufacturer for details)

Voltage Motor Code	Description	Switched (SW) or	Torque	RPM	Min X (mm)	Max drop	Headrail size		
-			remote (R)	Nm			(mm)	25mm	50mm
12 V DC	25SD1	Atlantic 12S - 12 V Double End				550mm [21 5/8"]	1600mm [63"]		
12 V DC	25501	Atlantic 125 - 12 V Double Enu	C)W/	4 5	32	630mm [24 13/16"]	2500mm [98 7/16"]		NL ZA
04.1/ 00	25SD2	Atlantia 040, 04 V Daubla Fad	SW	1.5	32	550mm [21 5/8"]	1600mm [63"]		N/A
24 V DC	25502	Atlantic 24S - 24 V Double End				630mm [24 13/16"]	2500mm [98 7/16"]		
24 V DC	24	Somfy Lw25-B83	SW	0.8	30	662 mm [26 1/16"]	3250 mm [127 15/16"]	~	N/A
12 V DC	038TW11	Atlantic 12R	CW/ / D	1.0		CEO mm [OE 9/16 II]	2000	NL /A	1
24 V DC	038TW12	Atlantic 24R	SW/R	1.2	26	650 mm [25 9/16 "]	3000 mm [118 <sup>1/8</sup> "]	N/A	v
24 V DC	S30D/S30R	Somfy Sonesse 30 DCT / RTS	SW / R	2	28				
230 V AC	S40W/S40R	Somfy Sonesse 40 WT / RTS	SW/R	9	12	616 mm [24 <sup>1/4</sup> "]	3250 mm [127 15/16"]	N/A	~
230 V AC	40W4	Pacific 230R WT 230v AC	SW	10	16	1			

Internal use only	Customised	SAFE 🗸	

### 

# **SKYVENETIAN** 25mm Wood slat

### Cord Tidy

Mandatory child safety device Fix to an adjacent wall, ensures taut chain or

continuous cord. Available in Chrome or Brushed Nickel with either a White or Black rubber insert.



### Guide wire hold down options

Dome: Chrome or Brushed Nickel


Flush mounted: Chrome, Brushed Nickel or Black


### Valance

Front facing Valance will be automatically colour and size matched based on order.



### ST6 Side Track Used to increase privacy, improve room darkening and help keep blinds secure 19.5[3/4"]





### **Head rail Colour Options**

		Headrail Type		
		VB25	VB50	
	White	~	~	
Standard Colour	China White		~	
	Black	~	~	
	Brown	~	~	
	Beige		~	
	Vanilla	~		
	Silver	~		

Custom colours are available, contact manufacuter for more details

