



HYBRID VENETIAN AND ROLLER BLIND FOR WINDOWS



Capture stunning views with Dometic Skyview, a hybrid venetian and roller blind, with the best of each blended into one. Skyview can be controlled by either cord, chain or powered operation. It is supported with optional guide wires or side tracks to prevent swinging and is available in a variety of fabric colours. Make the most of those great views with luxury powered control options, and operate your blinds at the touch of a button. The Skyview features tilting horizontal vanes of soft polyester suspended between two sheer fabric facings. This combination allows soft light diffusion and privacy without spoiling the view.

BENEFITS WITH SKYVIEW

- Open tilt for perfect views
- Closed tilt for privacy and light control
- Powered operation available with 12 V DC, 24 V DC or mains motors
- Hand held remote, wall switch or integration into the control system
- Available with guide wire control or side tracks for more secure deployment
- Soft, subtle finish with a contemporary style

SPECIFICATIONS

MANUAL CONTROLS	Chain Drive	
	Cord Drive	
POWERED CONTROLS	Volt: 12vDC / 24vDC / 110vAC / 230vAC	
	Radio Remote	
	Compatable with various automation	
	systems	
FABRIC	2" Sheer	
	2" Designer Inspired	
	2 ^{1/2} " Warm	
	2 ^{1/2*} Cool	
CORD TIDY	Chrome	
	Nickel	
FIXINGS	Top Fix	
	Face Fix	
RESTRAINTS	Free hanging	
	Guide wire	
	Side tracks	



HYBRID VENETIAN AND ROLLER BLIND FOR WINDOWS



ROLLERBLIND RANGE TECHNICAL DATA		0 0			
PRODUCT CODE: SVO	Lutron QS64	Atlantic	Somfy Rollup 28	Somfy Sonesse 30	
Marantia					
Motor Used	LS64	O38 480mm (18 ^{7/8} ")	RO28 440mm (17 ^{5/16} ")	\$30	
Min Width (X) Max Width (X)	471mm (18 ^{9/16} ") 3000mm (118 ^{1/8} ")	2000mm (78 ^{3/4} ")	2000mm (78 ^{3/4} ")	430mm (16 ^{15/16} ") 3000mm (118 ^{1/8} ")	
Max Drop (Y)	2500mm (98 ^{7/16} ")	2500mm (98 ^{7/16} ")	2000mm (78 ^{3/4} ")	2500mm (98 ^{7/16} ")	
Tube Diameter	42mm (1 ^{5/8} ")	38mm (1 ^{1/2} ")	38mm (1 ^{1/2} ")	38mm (1 ^{1/2} ")	
lube Diameter	4211111(1)			3611111(1)	
Free Hanging	RESTRAINTS ✓ ✓ ✓				
Guidewire	√	√	√ ·	√	
Side Tracks	√	X	X	√	
Side fidelis			^		
12vDC	Х	√	Х	Х	
24vDC	✓	✓	✓	✓	
110vAC	X	X	X	X	
230vAC	X	X	Х	X	
ROLLERBLIND RANGE TECHNICAL DATA PRODUCT CODE: SVO	Somfy Sonessi	e 40	Somfy Sonesse 50	Manual	
RANGE TECHNICAL DATA		e 40	Somfy Sonesse 50	Manual	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used	Somfy Sonesson		Somfy Sonesse 50		
RANGE TECHNICAL DATA PRODUCT CODE: SVO	Somfy Sonesso	/16")	Somfy Sonesse 50	Manual CHAIN/CORD	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X)	Somfy Sonesson \$40 580mm (22 ¹³)	/16°) 1/8°)	Somfy Sonesse 50 \$50 755mm (29 ^{3/4*})	Manual CHAIN/CORD 400mm (15 ^{3/4})	
PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X)	Somfy Sonesson 540 580mm (22 ¹³ 3000mm (118	/16°) 1/8°) /16°)	Somfy Sonesse 50 \$50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*})	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*})	
PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y)	Somfy Sonesson S40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷)	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 \$50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*})	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*})	
PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y)	Somfy Sonesson S40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷)	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 S50 755mm (29 ^{3/4"}) 3000mm (118 ^{1/8"}) 2500mm (98 ^{7/16"}) 50mm (2")	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*})	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y) Tube Diameter	Somfy Sonesson \$40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷) 40mm (1 ⁹ /16	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 S50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*}) 50mm (2*)	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*}) 2000mm (78 ^{3/4*}) 38mm (1 ^{1/2*})	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y) Tube Diameter Free Hanging	Somfy Sonesson \$40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷ 40mm (1 ^{9/16}	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 S50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*}) 50mm (2*)	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*}) 2000mm (78 ^{3/4*})	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y) Tube Diameter Free Hanging Guidewire	Somfy Sonesson \$40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷ 40mm (1 ^{9/16}	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 \$50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*}) 50mm (2*) TRAINTS ✓ X	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*}) 2000mm (78 ^{3/4*}) 38mm (1 ^{1/2*})	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y) Tube Diameter Free Hanging Guidewire Side Tracks	Somfy Sonesson \$40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷ 40mm (1 ^{9/16}	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 S50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*}) 50mm (2*) TRAINTS X	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*}) 2000mm (78 ^{3/4*}) 38mm (1 ^{1/2*})	
RANGE TECHNICAL DATA PRODUCT CODE: SVO Motor Used Min Width (X) Max Width (X) Max Drop (Y) Tube Diameter Free Hanging Guidewire Side Tracks 12vDC	Somfy Sonesson S40 580mm (22 ¹³ , 3000mm (118 2500mm (98 ⁷ 40mm (1 ⁹ /16	/ ^{/16} ") 1/8") //16")	Somfy Sonesse 50 S50 755mm (29 ^{3/4*}) 3000mm (118 ^{1/8*}) 2500mm (98 ^{7/16*}) 50mm (2*) TRAINTS	Manual CHAIN/CORD 400mm (15 ^{3/4*}) 2000mm (78 ^{3/4*}) 2000mm (78 ^{3/4*}) 38mm (1 ^{1/2*})	