



## Intended use

The universal fixing kit CFX-UFK (belt system) is used for fixing CFX coolers securely in the luggage compartment.

## Safety notes

**Please observe the prescribed safety instructions and stipulations from the vehicle manufacturer and service workshops.**

- When fitting, ensure that the distances are correct (fig. 2). Otherwise the cooler cannot be fixed properly.
- To prevent damage when drilling, make sure that there is sufficient space on the other side for the drill head to come out.
- Deburr all drill holes and treat them with a rust-protection agent.
- Do not use the fixing kit if it is visibly damaged.
- Always ensure sufficient ventilation so that the heat generated from the cooler during operation can dissipate. Make sure that the device is sufficiently far away from walls and other objects so that the air can circulate.

- Ensure that the ventilation openings on the cooler are not covered.
- Secure the fixing kit in such a way that it cannot become loose under any circumstances (sudden braking, accidents) and cause injuries to the occupants of the vehicle.
- Secure any parts of the system covered by panelling in such a manner that they cannot become loose or damage other parts and cables, or impair vehicle functions.
- Always follow the safety instructions of the vehicle manufacturer. Some work may only be performed by qualified specialists.

## Scope of delivery

Pos. in fig. <b>1</b>	Quantity	Description
1	4	Lashing belt
2	4	Lashing eyelet
3-5	-	Fastening and installation material

## Mounting the fixing kit

- Mark the drill holes for the lashing eyelets and drill 10 mm holes (fig. **2** 1).
- Fix each of the four lashing eyelets with two washers, a bolt and a nut (fig. **2** 2).

## Using the fixing kit



### Caution! Risk of damage!

Over-tightening the lashing belts can damage the handles on the cooler. Tighten the lashing belts just enough so that the cooler is fixed securely to the loading surface.

- Attach the lashing belts to the lashing eyelets (fig. **3** 1).
- Wind the lashing belts around the handles of the cooler (fig. **3** 2).
- Insert the ends of the lashing belts in the clamp locks and pull them tight (fig. **3** 3).

## Technical data

	CFX-UFK
Ref. no.:	9108300002
Length of lashing belts:	1.5 m
Tensile force of lashing belts:	250 daN